Literature Validation of a Cascading Molecular Reactor Cage Architecture for a Molecular Manufacturing Device

By Colin Kakama.
20th April 2026.

Table of Contents

1. Background
2. Polymer Build Sequence
3. Crystalline Microfibril Assembly
4. Electro-mechanical Control of Nanoreactors
5. Schematic of the Cages Inside of a Mechanically Active Matrix While in Operation
6. References

Background

Much of the background of this report is a summary of the ideas covered in this article. Feel free to look there for more in-depth context not covered in this section.

Here goes:

The core premise of this work is that reliable part production is the first domino in any nanomanufacturing stack. Earlier work explored thermoplastic nanoimprinting as a route to this, but that approach runs into a hard constraint: stiffness, precision, and processability are difficult to achieve simultaneously from the same material class. This report explores a chemistry-first alternative, one that pushes cavity-confined fabrication down from the nanoparticle scale into the supramolecular regime.

The central concept is that an engineered molecular cage, shaped to stabilize a specific transition state geometry, can function as a nanoreactor: a cavity that biases which bonds form and how, rather than merely containing reactants. Stringing a cascade of such nanoreactors along a substrate and coupling them to an actuation and sensing system produces the bones of a molecular manufacturing platform. This report documents the literature basis for four components of that platform: the polymer build sequence, crystalline microfibril assembly, electro-mechanical control of the nanoreactors, and the physical arrangement of cages inside a mechanically active matrix. The target material for this worked example is cellulose nanocrystals, chosen for their combination of high stiffness(~150+ GPa) along the chain axis and biodegradability, a rare pairing that makes them a practical first target for nanomanufactured structural parts intended for near term bioengineering applications.

Polymer Build Sequence

Note: This section describes an untested hypothesis. Unlike the cage geometry and microfibril assembly sections, which are grounded in existing literature and can be computationally validated with current tools, the build sequence for stepwise chain growth inside a cavity-confined nanoreactor has no direct precedent in the literature. Validating it requires dedicated simulation and, eventually, experiment. It is the open problem that defines the next phase of this work.

The core idea: open, add, exit, reset

For a cellulose chain to grow inside the nanoreactor cage one glucose unit at a time, the cage needs to run a repeating four-step cycle. That is:

1. First, the cage opens.
2. Second, a new glucose unit enters.
3. Third, a beta-1,4 glycosidic bond forms between the incoming glucose and the growing chain end.
4. And finally, fourth, the finished chain end threads out through the exit channel while the cage resets for the next addition.

The part we understand reasonably well is step three, because beta-1,4 bond formation chemistry has been studied extensively in other contexts. What we do not yet understand is how to drive steps one through four in a coordinated way inside a synthetic cage, with no enzyme doing the work. That is the gap.

The open and push

The mechanical side of the cycle works as follows. When the cage opens in response to its actuation stimulus, whether electrical or thermal, the finished glucose unit needs a reason to leave rather than just sitting there. One way to give it that reason is to introduce a small molecule alongside the actuation signal, something that is either electrostatically repulsive to the existing chain end or that competes for the active site and displaces the product. This molecule could be purely functional(just a push), or it could serve double duty as a reactant or catalyst for the next bond formation event.

Candidate agents for stepwise beta-1,4 addition

By adding a catalytic agent **to the preloaded glucose molecule alone, both the feedstock and in-cage glucose subunits, or even the cage nanoreactor itself,** one can promote bond formation between two glucose subunits.

What makes this largely a hypothesis rather than a design is that we do not yet know what the catalytic agent should be. However, informed speculation provides the following as benchmarks:

1. **Cellodextrin phosphorylase chemistry:** A synthetic organocatalyst that mimics the glycosylation events of the cellodextrin phosphorylase(CDP) enzyme. CDP catalyzes iterative beta-1,4-glycosylation using alpha-D-glucose-1-phosphate as the donor substrate, and is unique among phosphorylases in performing repeated glycosylation events on the same acceptor chain[7]
2. **UDP activated glucose linking**: A synthetic mimicry of the chemistry of the cellulose synthase enzyme that turns UDP activated glucose into cellulose[13].
3. **The cage itself:** A second possibility is that the catalytic agent is not molecular at all, but electrostatic. If the cage walls can be engineered to create a local electric field that stabilizes the oxocarbenium-like transition state of the glycosidic bond, the cage itself becomes the catalyst. The small molecule entering with the actuation signal would then serve only the mechanical purpose of pushing the product out, not the chemical one.

None of these are confirmed. At this stage, we are in the territory of educated candidates rather than validated mechanisms. Identifying which, if any, of these approaches can be made to work inside a synthetic cage at the relevant size scale is the central question for the next experimental phase.

Polymer chain translocation

Singh et al describe translocation of a polymer chain across a nanopore as a phenomena that can be achieved both passively(through innate entropic activity of the substrates) and actively(by setting up a force gradient across the pore and or by applying a pulling force on one end of the polymer)[12].
For our context, by modulating these properties with accessories in close proximity to the cage, the same controlled motion events could be achieved for a glucose polymer.

Crystalline Microfibril Assembly

Once individual cellulose chains have been produced by the reactor cascade, the next challenge is getting them to pack into a crystalline microfibril. This section covers two categories of approach: passive assembly, where chains come together on their own through their natural chemistry, and active assembly, where an external tool or agent is used to bring them into alignment.

Passive Assembly

Innately: Cellulose chains have a natural tendency to pack together. Each glucose monomer carries hydroxyl groups that form hydrogen bonds both within a single chain and between neighboring chains. Intrachain hydrogen bonds raise the stiffness of each polymer, while an interchain hydrogen bond network links chains together to form two-dimensional sheets[1]. This behavior is extremely well characterized for the cellulose Iβ polymorph, which is the dominant crystalline form in higher plants. The crystal structure of cellulose Iβ consists

of two parallel chains organized in sheets, with the hydrogen bond network maintaining the chains in their packed arrangement[2].

It is worth noting that hydrogen bonding is not the only force holding the crystal together. Crystalline cellulose is held together not just by hydrogen bonding, but also by dispersion forces and electrostatic attraction[3]. The relative contribution of each force has been debated in the literature, but the practical point for our purposes is that once chains are placed in close parallel alignment, the combined effect of all these interactions is enough to drive spontaneous crystallization. This gives us a passive assembly mechanism to start from.

If chains exiting the reactor cages can be directed into a region where they run parallel to one another, they should self-assemble into a microfibril without requiring further intervention at each step.

By functional groups: To improve the geometry of this assembly, we can introduce functional groups at the tips and along the intervals of the chains. The strategy is borrowed from how thiol groups are used in molecular self-assembly: a sulfur binding group can anchor a molecule to a surface while the functional head group can be designed to provide virtually any surface chemistry or binding capacity[4]. Applied to our chains, sulfur-containing groups or other reactive handles placed at chain ends and at regular intervals along the backbone can be used to guide how chains recognize and bind to one another. This is an iterative refinement process. Groups will be added and tested carefully, with the constraint that they must not disrupt the crystallinity of the resulting microfibril. Crystallinity is the source of the mechanical properties we are targeting, so any functionalization that disorders the packing defeats the purpose.

Active Assembly

Passive chemistry alone may not be sufficient to reliably align chains with the precision needed, especially in early experimental runs. For this reason, active assembly methods are planned as a parallel track.

SPM: The first method is scanning probe microscopy (SPM). SPM put single-atom and single-molecule manipulation into practice for the first time, and extending this controlled manipulation to larger molecules multiplies the potential of engineered nanostructures[5]. In our context, SPM would be used to physically position chains and nudge them into parallel alignment on a substrate, allowing us to observe the crystallization process directly and refine our understanding of what geometry is needed at the assembly stage. This is a slow, manual method, and it is intended for early experimental validation rather than scalable production.

Using CNCs themselves: The longer-term active assembly method uses cellulose nanoparticles as templating agents. A freshly produced chain placed near the surface of an existing CNC has a natural tendency to register with it, adding to the crystal face through the same hydrogen bonding and dispersion forces described above. MD simulations of oligomer self-assembly on a cellulose Iβ microfibril show that the process involves structural

recognition of the crystal surface and the formation of hydrogen bonds, with longer oligomers forming more stable complexes[6].

This means cellulose nanoparticle surfaces can latch on to glucose chains and mechanically guide them into the correct packing geometry.

Electro-mechanical Control of Nanoreactors

The control system for the nanoreactor platform borrows its core logic from nanopore sensing, a well-established field in which a voltage applied across a membrane containing a small pore drives ions through it, and molecules passing through the pore produce measurable disruptions in that ionic current. A nanopore is set in an electrically resistant membrane so that an ionic current passes through when a voltage is applied across it. When a molecule comes into contact with the pore, this disrupts the current, and that disruption can be measured to identify the molecule[8]. Our system uses this same principle, but adapted for a manufacturing context rather than a sensing one.

Species detection

The first function this gives us is monitoring. Just as nanopores register the presence of a molecule by the characteristic dip in current it produces as it enters or exits the pore, our system can register when glucose enters a cage and when a chain end exits. A transmembrane voltage bias drives charged solutes through the nanopore, and the steric constraints of the nanopore ensure that only one molecule is loaded at a time[9]. Adapted to our context, this means we can use the current signal to track each step of the manufacturing cycle in real time, knowing when a cage is loaded, when a bond formation event has occurred, and when the product has exited. This is a significant advantage over running the chemistry blind.

Mechanical actuation via a piezoelectric matrix

The second function is actuation. The cages need to open and close on demand, and applying that force at the individual cage level from outside the system is not practical. The proposed solution is to embed the cages in a piezoelectric matrix.

Piezoelectric materials convert between mechanical energy and electrical energy: when mechanical deformation occurs they produce an electrical signal, and when an electric field is applied they produce a strain[10]. This two-way transduction is what we need. By applying a voltage to the matrix, we deform it, and that deformation is transmitted to the cages embedded within it. The cages open. When the voltage is removed or reversed, the matrix relaxes and the cages close. This gives us electrical control over a mechanical process at the nanoscale, without needing to address each cage individually.

Figure 1. Deformation modes of piezo materials

Source: Thorlabs, https://www.thorlabs.com/piezoelectric-tutorial?tabName=Overview



There is direct precedent for this kind of piezo-driven pore actuation. Rapid piezoelectric actuation of a single elastomeric micropore has been demonstrated, with ionic conductance measured while the pore was opened and closed in both stepwise and oscillatory modes[11]. That work operated at the micropore scale, but the underlying principle (a piezo element deforming a surrounding matrix to change pore geometry) is exactly the mechanism we are proposing to apply at the nanoscale.

The physical arrangement

The proposed hardware layout is as follows. Multiple nanoreactor cages are immobilized within nanopores in a piezoelectric matrix. Each cage sits inside a pore, held in place by covalent anchoring as described in the cage geometry section. Functional accessories, such as molecules that help guide glucose in and chain ends out, are immobilized on the exposed outer surface of the matrix and extend down into the pores where the cages sit. When voltage is applied, the matrix compresses, the cage opens, the accessory molecules help usher the product out and the new substrate in, and the cycle runs. The ionic current across the pore registers each step.

This arrangement means the same electrode system handles both actuation and sensing. The voltage drives the mechanical cycle. The current signal reads it back. One interface, two functions.

Schematic of the Cages Inside of a Mechanically Active Matrix While in Operation

Figure 2: Glucose polymerization by nanoreactors



Molecular cage geometry sourced from Wikipedia. Glucose polymer structure from https://doi.org/10.1007/s11270-021-05245-6

References

1. Shen T, Gnanakaran S, **The Stability of Cellulose: A Statistical Perspective from a Coarse-Grained Model of Hydrogen-Bond Networks**, Biophysical Journal, 96, 3032-3040, DOI: 10.1016/j.bpj.2008.12.3953
2. **Crystal Structure and Hydrogen-Bonding System in Cellulose Iβ from Synchrotron X-ray and Neutron Fiber Diffraction**, Yoshiharu Nishiyama, Paul Langan, Henri Chanzy, https://pubs.acs.org/doi/10.1021/ja0257319
3. Jarvis, M.C. **Hydrogen bonding and other non-covalent interactions at the surfaces of cellulose microfibrils**. *Cellulose* 30, 667–687 (2023). https://doi.org/10.1007/s10570-022-04954-3
4. **Self-Assembled Monolayers: Advantages of Pure Alkanethiols**, Maxi Boeckl, Dr., Daniel Graham, Dr., Sigma-Aldrich, https://www.sigmaaldrich.com/UG/en/technical-documents/technical-article/materials-science-and-engineering/organic-electronics/self-assembled-monolayers
5. **Patterning a hydrogen-bonded molecular monolayer with a hand-controlled scanning probe microscope**, Matthew F. B. Green, Taner Esat, Christian Wagner, Philipp Leinen, Alexander Grötsch, F. Stefan Tautz and Ruslan Temirov, Beilstein J. Nanotechnol. 2014, 5, 1926–1932, https://doi.org/10.3762/bjnano.5.203

6. Thu, T.T.M.; Moreira, R.A.; Weber, S.A.L.; Poma, A.B. **Molecular Insight into the Self-Assembly Process of Cellulose Iβ Microfibril**. Int. J. Mol. Sci. 2022, 23, 8505. https://doi.org/10.3390/ijms23158505
7. Bernd Nidetzky, Chao Zhong, **Phosphorylase-catalyzed bottom-up synthesis of short-chain soluble cello-oligosaccharides and property-tunable cellulosic materials**, Biotechnology Advances, Volume 51, 2021, 107633, ISSN 0734-9750, https://doi.org/10.1016/j.biotechadv.2020.107633
8. **Nanopore sensing** - how it works, Oxford Nanopore Technologies, https://nanoporetech.com/document/nanopore-sensing
9. Aksimentiev A. **Deciphering ionic current signatures of DNA transport through a nanopore**. Nanoscale. 2010 Apr;2(4):468-83. doi: 10.1039/b9nr00275h. Epub 2010 Feb 2. PMID: 20644747; PMCID: PMC2909628.
10. Chen, B., Feng, Z., Yao, FZ. *et al.* **Flexible piezoelectrics: integration of sensing, actuating and energy harvesting**. *npj Flex Electron* 9, 58 (2025). https://doi.org/10.1038/s41528-025-00432-5
11. Murray L. Jansen, Geoff R. Willmott, Ingrid Hoek, W. Mike Arnold, **Fast piezoelectric actuation of an elastomeric micropore**, Measurement, Volume 46, Issue 9, 2013, Pages 3560-3567, ISSN 0263-2241, https://doi.org/10.1016/j.measurement.2013.05.023
12. Singh SL, Chauhan K, Bharadwaj AS, Kishore V, Laux P, Luch A, Singh AV. **Polymer Translocation and Nanopore Sequencing: A Review of Advances and Challenges**. International Journal of Molecular Sciences. 2023; 24(7):6153. https://doi.org/10.3390/ijms24076153
13. **Cellulose synthase (UDP-forming)**, Wikipedia, https://en.wikipedia.org/wiki/Cellulose_synthase_(UDP-forming)#Activity:~:text=Further%20reading-,Cellulose%20synthase%20(UDP%2Dforming),-7%20languages